

Quick installation guide H-8ASI-IP gateway

- 1) Install NMS_EN Management software located on the CD or website https://thorbroadcast.com/upload/files/46/nms-en4.84.exe
- 2) Add Freq Node
- 3) Add Device select from the list 8*ASI-8* IP Gateway
- 4) Type Name
- 5) Type Device NMS IP address

iystem(<u>S</u>) De	evice(<u>E)</u> Operate	(V) Setting(C)	Help(<u>H</u>)							
pen Device	Save Device	Add Freq Node	Add Device	Edit Device	X Del Device	Save Config	Restore Conf.	Reload Config	Import Config	Export Config
li <i>st</i> aaa	451	8*ASI-8*I	Gateway							
H-8A	ISI-IP	Channe	:I-1							
	Edit Device						×	Port	t: 10002 🔽	Enable
-	Device	e Type 8*ASI	8*IP Gatewa	у				Port	t: 10004 🔽	Enable
	IP Ac	Name H-8AS	-IP 168.0.2	53 Por	t: 2009		-	Port	t: 10006 🔽	Enable
		[ок	7	Cancel	1		Port	t 10008 🔽	Enable

Set the multicast IP addresses and port numbers – the output is from the Data IP port "TS over IP"

🐶 Network Management Software	e(Version:4.84)						-	o	×		
System(S) Device(E) Operate(V) Setting(C) Help(H)										
Open Device Save Device A	Add Freq Node Add Device	Edit Device Del I	X Save Config Re	store Conf. Reload Config Im	Config Export Config						
E-Ks+ aaa	8*ASI-8*IP Gateway										
D TP TO ASI	Channel 1										
THE ANSI IT	BitRate: 19	^{3.078} Mbps D	estination IP: 224.2	2 . 2 Port: 10	002 🔽 Enable						
	Channel-2										
	● BitRate: [19.078] Mbps Destination IP: 224.2.2.4 Port: [10004 F Enable										
	Channel-3										
	● BiRate: 0.000 Mbps Destination IP: 224.2.2.6 Port: 10006 ▼ Enable										
	Channel-4										
	BitRate: 0.	● BitRate: 0.000 Mbps Destination IP: 224.2.2.8 Port: 10008 F Enable									
	Channel-5										
	BitRate: 0.000 Mbps Destination IP: 224. 2 . 2 . 10 Port: 10010 F Enable										
	Channel-5										
	BitRate: 0.	.000 Mbps D	estination IP: 224.2	. 2 . 12 Port: 10	012 🔽 Enable						
	Channel-7										
	BitRate: 0.	000 Mbps D	estination IP: 224. 2	. 2 . 14 Port: 10	014 🔽 Enable						
	Channel-8										
	BitRate: 0.000 Mbps Destination IP: 224. 2. 2. 16 Port: 10016 F Enable										
	Local IP Adress										
	IP Adress: 192.1	IP Adress: 192.168. 1 223 Subnet 255.255.0 Get Set									
Type: 8*ASI-8*IP Gateway	MAC Adress: 00	-08-09-0a-0b-0c Auto	Generate Source Port:	1234							
Name: H-8ASI-IP IP Add.: 192.168.0.253	Device Name	IP Address	Device Type	Alarm Info	Alarm Time						
(10 Port: 2009	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Save config	2023-3-8 11:18:30						
HW Ver.: 1.21	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Save config succeed!	2023-3-8 11:18:37						
SW Ver.: 4.03	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device offline	2023-3-8 11:19:35						
Code: 000000tc	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device online	2023-3-8 11:19:40						
	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device offline	2023-3-8 11:20:20						
	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device online	2023-3-8 11:21:26						
	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device offline	2023-3-8 11:23:45						
	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device online	2023-3-8 11:24:25				- 1		
	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device offline	2023-3-8 11:25:35						
	CH-8ASI-IP	192.168.0.253	8*ASI-8*IP Gateway	Device online	2023-3-8 11:35:21						
Ready								Nu	mber		
44°F Clear			📕 🔉 😐	🔚 🖉 💽 🔛	🧛 🤒 O 📟	🖂 🛓	^ ^{Ce} 🖫	Co 11:4 3/8	42 AM		

www.thorbroadcast.com 800-521-8467 Ext 2 sales@thorfiber.com